

LDC LP No. 01 Dtd 16th April 2025

4 of 12

POLYCAB		POLYCAB INDIA LIMITED								
IDEAS. CONNECTED.		LDC LP No. 01/2025-26 Dtd : 16th April 2025								
Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts			Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694:2010							
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Price in Rs./100m)		(Price in Rs./100m)					
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/2	5	1435	24	3795	5115	6485	5	8035	9595
0.75	24/2	8	2015	24	5060	6900	8790	5	11355	13700
1	32/2	13	2535	20	6340	8735	11200	5	14625	17615
1.5	30/25	17	3630	16	8590	12210	15605	5	19985	24325
2.5	50/25	24	6015	12	14100	19200	25900	4	32500	39300
4	56/3	30	9160	8	20600	29500	38900		51500	61700
6	84/3	38	13800	6	30200	43200	57000		75900	91100
10	80/4	52	24400	1	51200	75100	99300		130900	
16	126/4	70	37800	1	81600	118900	156400		201100	
25	196/4	88	59200	1	135200	196600	257100		365100	
35	276/4	110	82800	1	188300	273200	359600		500400	
50	396/4	145	117800	1	267300	389100	513700		724400	
70	354/5	215	166900	1	379300	539700	713800		990600	
95	484/5	260	220100	1		765100	1009300			
120	608/5	305	283100	1		971400	1282100			
150	750/5	355	354900	1		1214400	1602900			
185	925/5	415	441100	1		1495500	1976700			
240	1210/5	500	576200	1		1930500	2555400			
300	1527/5	585	721100	1		2409000	3190000			
400	2036/5	695	960800	1		3209800	4225400			
500			1201900	1						
630			1550200	1						

POLYCAB		POLYCAB INDIA LIMITED				
IDEAS. CONNECTED.		LDC LP No. 01/2025-26 Dtd : 16th April 2025				
Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cables conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts			Price in Rs./100 Mtrs.			
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			7 Core	8 Core	10 Core	12 Core
0.5	16/2	5	10800	12800	15900	18600
0.75	24/2	8	15300	18000	22600	26300
1	32/2	13	19900	23100	28700	34100
1.5	30/25	17	27400	31600	40300	47400
2.5	50/25	24	45100	53600	65800	79000
4	56/3	30	74400			

Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cables conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts			Price in Rs./100 Mtrs.			
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			14 Core	16 Core	19 Core	24 Core

LDC LP No. 01 Dtd 16th April 2025

3 of 12

POLYCAB		POLYCAB INDIA LIMITED						
IDEAS. CONNECTED.		LDC LP No. 01/2025-26 Dtd : 16th April 2025						
Polycab FR PVC Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694-2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts			(Price in Rs./100m)		Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694-2010			
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Price in Rs./100m)		(Price in Rs./100m)			
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing
0.5	16/2	5	1400	24	3570	4895	6260	5
0.75	24/2	8	1965	24	4770	6630	8520	5
1	32/2	13	2500	20	6070	8430	10900	5
1.5	30/2.5	17	3605	16	8250	11850	15350	5
2.5	50/2.5	24	5925	12	13600	18700	25300	4
4	56/3	30	9100	8	20000	28800	38300	
6	84/3	38	13600	6	29500	42400	56300	
10	80/4	52	23900	1	50300	74000	97700	
16	126/4	70	37200	1	79500	116200	153500	
25	196/4	88	58500	1	132500	192800	251800	
35	276/4	110	81900	1	184500	267900	352100	
50	396/4	145	116800	1	261800	381600	503900	
70	354/5	215	165000	1	372000	529300	699700	
95	484/5	260	217700	1				
120	608/5	305	280700	1				
150	750/5	355	351300	1				
185	925/5	415	437100	1				
240	1210/5	500	570600	1				
300	1527/5	585	713900	1				
400	2036/5	695	951200	1				
500			1190000	1				
630			1534800	1				

POLYCAB		POLYCAB INDIA LIMITED								
IDEAS. CONNECTED.		LDC LP No. 01/2025-26 Dtd : 16th April 2025								
Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694-2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts			(Price in Rs./100m)		Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694-2010					
Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Price in Rs./100m)		(Price in Rs./100m)					
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/2	5	1435	24	3795	5115	6485	5	8035	9595
0.75	24/2	8	2015	24	5060	6900	8790	5	11355	13700
1	32/2	13	2535	20	6340	8735	11200	5	14625	17615
1.5	30/2.5	17	3630	16	8590	12210	15605	5	19985	24325
2.5	50/2.5	24	6015	12	14100	19200	25900	4	32500	39300
4	56/3	30	9160	8	20600	29500	38900		51500	61700
6	84/3	38	13800	6	30200	43200	57000		75900	91100
10	80/4	52	24400	1	51200	75100	99300		130900	
16	126/4	70	37800	1	81600	118900	156400		201100	

LDC LP No. 01 Dtd 16th April 2025

5 of 12

150	750/5	355	354900	1	1214400	1602900		
185	925/5	415	441100	1	1495500	1976700		
		500	576200	1	1930500	2555400		
		585	721100	1	2409000	3190000		
		695	960800	1	3209800	4225400		
			1201900	1				
			1550200	1				

Page 3 of 11

POLYCAB POLYCAB INDIA LIMITED
EXCEL CONNECTED
 LDC LP No. 01/2025-26 Dtd : 16th April 2025

Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cables conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			7 Core	8 Core	10 Core	12 Core
0.5	16/2	5	10800	12800	15900	18600
0.75	24/2	8	15300	18000	22600	26300
1	32/2	13	19900	23100	28700	34100
1.5	30/25	17	27400	31600	40300	47400
2.5	50/25	24	45100	53600	65800	79000
4	56/3	30	74400			

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Price in Rs./100 Mtrs.			
			14 Core	16 Core	19 Core	24 Core
0.5	16/2	5	21400	24400	28200	35600
0.75	24/2	8	30900	34800	41200	51400
1	32/2	13	39700	45200	53100	66500
1.5	30/25	17	56100	64700	75100	96200
2.5	50/25	24	91800	104900	121500	157400

Page 4 of 11

POLYCAB POLYCAB INDIA LIMITED
EXCEL CONNECTED
 LDC LP No. 01/2025-26 Dtd : 16th April 2025

Polycab Multi Strand Bare Copper conductor XLPE Insulated PVC Sheathed Cables

Nominal Area	No./Dia of Strands	Current rating in Air at 40°C	Cu Conductor Unarmoured Cables		Cu Conductor Aluminium Armouring Cables	
			Rs/100 Mtr.	Rs/100 Mtr.	Rs/100 Mtr.	Rs/100 Mtr.
mm ²	No./mm	CS	18300		25000	
A	A4/11	CS				